

- Pure glass touchscreens for optimal image quality
- Multiple mounting options
- Commercial durability
- 3 year standard warranty



1940L 19" LED Open-Frame Touchmonitor

Available with either IntelliTouch Plus multi-touch surface acoustic wave touchscreen technology or projected capacitive for a no bezel look, the Elo 1940L provides stable "driftfree" operation with outstanding image clarity, resolution, and light transmission—for an accurate touch response and vivid images! The 1940L is an ideal solution for many public applications including gift registry, food ordering, airline check-in, DVD and bill-paying kiosks.

Wide-aspect 16:9 displays like the Elo 1940L support extra content on the screen and are becoming preferred where a large touch activated surface area is desired. Increasingly popular in public venue environments, these displays deliver a high-definition

cinematic-like experience. The new 1940L features an energy-saving LED backlight, 170°(h) x 160°(v) viewing angle and 1000:1 contrast ratio for a bright display in a thin, compact, space-saving mechanical design.

The 1940L has a compact form factor with optional rack and front-mount bezels for easy integration. It features a unique injection-molded mini-bezel with a virtually invisible water-resistant seal. We are committed to delivering a quality product and as a result the 1940L is backed by a three-year warranty.



Features:

- Long lasting product life—enclosure controlled by Elo specifications
- Integrated precision mini-bezel with water-resistant 0.5 mm seal (IntelliTouch Plus only)
- Mounting options include rack and front-mount
- Compact mechanical design
- Choice of IntelliTouch Plus multi-touch or projected capacitive (PCAP) touchscreen technology
- LED backlight uses 25% less power
- Worldwide agency approvals

Applications:

- Gaming machines
- Information kiosks
- Self-service and ticketing

About Elo

Elo founders pioneered the touch screen over 40 years ago. Today, Elo Touch Solutions is a leading global supplier of touch-enabled technology, products and industry solutions. The Elo portfolio encompasses the broadest selection of OEM touchscreen components, touchmonitors, and all-in-one touchcomputers for the demanding requirements of diverse markets, including gaming machines, hospitality systems, industrial automation, interactive kiosks, healthcare, office equipment, point of sale terminals, retail displays, and transportation applications. The Elo touch experience has consistently stood for quality, reliability and innovation with over 20 million installations worldwide.

1940L 19" LED Open-Frame Touchmonitor

Model	1940L
Active Display Area	16.13" x 9.07" (409.8mm x 230.4mm)
Dimensions	17.58" x 10.58" x 1.51" (446.7mm x 268.8mm x 38.5mm) max
LCD Technology	Active matrix TFT LCD with LED backlighting
Diagonal Size	18.5"
On-Screen Display (OSD)	Accessible through switches on the unit's tethered OSD Control Keypad. Controls: Menu, Up, Down, Select, Power Settings: Brightness, Contrast, Clock, Phase, H-position, Vposition, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, OSD H-Position, OSD V-Position, Recall Defaults, Video Source Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power
Mounting Options*	VESA 4-hole 75mm mounting interface on rear of unit; 2-hole mounting interface on all 4 sides
Native Resolution	1366x768
Aspect Ratio	16:9
Preset Video Timings	720 x 350 at 70Hz; 720 x 400 at 70Hz; 640 x 480 at 60, 72, 75Hz; 800 x 600 at 56, 60, 72, 75Hz; 800 x 500 at 60Hz; 832 x 624 at 75Hz; 1024 x 768 at 60, 70, 75Hz; 1280 x 800 at 60Hz; 1280 x 960 at 60Hz; 1280 x 1024 at 60, 75Hz; 1366 x 768 at 60Hz
Number of Colors	16.7 million
Brightness (typical)	LCD Panel: 250 nits; with IntelliTouch Plus: 225 nits; with PCAP: 225 nits
Response Time (Tr + Tf) (typical)	5 ms
Viewing Angle (typical)	Horizontal: 170°; Vertical: 160°
Contrast Ratio (typical)	1000:1
Video	Analog VGA on Female DE-15 connector; Digital DVI on Female DVI-D connector Input Video Horizontal Sync frequency range: 31.5-80KHz Input Video Vertical Sync (frame rate) frequency range: 50-75Hz
Power	External DC—optional power brick (sold separately) Monitor input power connector: Coaxial power jack (2mm pin outer diameter, 6.4mm barrel inner diameter) Monitor input power signal specifications: 12VDC ± 5% Adapter input connector: IEC 60320 C14 Adapter input voltage range: 100-240VAC, 50/60Hz Power Consumption: ON (monitor + AC/DC adapter at 230V/50Hz): 19W(typ), 25W (max); SLEEP (monitor + AC/DC adapter at 230V/50Hz): 2.0W; OFF (monitor + AC/DC adapter at 230V/50Hz): 1.0W
Audio	N/A (No audio functionality)
Weight	Unpackaged: 7.38 lbs (3.35kg); Packaged: 10.58 lbs (4.8kg)
Shipping Dimensions	21.45" (L) x 14.37" (W) x 5.5" (H) (54.5cm x 36.5cm x 14cm)
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 140°F (-20°C to 60°C)
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-90%
Regulatory approvals and declarations	C-Tick, cUL, IC, CCC, CE, VCCI, KCC, CoC, BSMI; UL, FCC; CB, RoHS, WEEE, IMERC
Warranty	3 years
MTBF	50,000 hours demonstrated

*See dimensional drawings for details.

Ordering Information

Model	Part Number	Technology	Interface	Surface Treatment	Availability
1940L	E855244	IntelliTouch Plus	USB	Clear	Worldwide
	E065303	Projected Capacitive	USB	Clear	Worldwide

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America

Elo Touch Solutions
1033 McCarthy Boulevard
Milpitas, CA 95035

800-ELO-TOUCH

Tel +1 408 597 8000

Fax +1 408 597 8001

customerservice@elotouch.com

Europe

Tel +32 (0)16 70 45 00

Fax +32 (0)16 70 45 49

elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385

Fax +86 (21) 3329 1400

www.elotouch.com.cn

Latin America

Tel 786-923-0251

Fax 305-931-0124

www.elotouch.com

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo) and Elo Touch Solutions are trademarks of Elo Touch Solutions, Inc. Copyright 2014 Elo Touch Solutions, Inc. All rights reserved. DS000065, rev B 05/14

