



15A1 15" All-in-one Touchcomputer

Compact, Reliable and Stable for POS Applications

Elo TouchSystems 15A1 15" all-in-one touchcomputer expands the company's high profile family of reliable, easy-to-integrate multifunction touch solutions that can meet the requirements of any systems integrator, OEM or value-added reseller. Retail-rugged, the 15A1 features a spill-resistant sealing, a stable tilt base that is removable or reversible for wall mounting, a VESA mounting option, cables hidden from user view, and side controls with lockout for public use.

Touch options include a choice of Elo TouchSystems newest, breakthrough touch technology, Acoustic Pulse Recognition, AccuTouch five-wire resistive, IntelliTouch surface wave or CarrollTouch infrared. Additional options include a three-track magnetic stripe reader (MSR) and rear-facing customer display. Operating system options support Microsoft® Windows® XP Professional Service Pack 2 and Microsoft Windows Embedded for Point of Service (WEPOS).

The silent, fanless design of the 15A1 and its compact integrated peripherals, make this all-in-one touchcomputer an ideal choice for point-of-sales, kiosks and point-of-interest applications.

Features

- Space saving, integrated, all-in-one touchcomputer in a standard 15" LCD display
- Silent, fanless Intel® Celeron® M design, ideal for POS, kiosks and POI applications
- Industry standard VESA mounting options, configurable as a desktop or wall-mount
- Choice of Microsoft Windows Embedded for POS (WEPOS) or Microsoft Windows XP Professional
- Available with AccuTouch five-wire resistive, CarrollTouch infrared, IntelliTouch surface-wave or Acoustic Pulse Recognition (APR) touch technology
- One Ethernet, two serial, and four high-speed USB 2.0 ports for maximum expansion
- "Designed for touch" for public access with cables hidden from user's view and controls with lockout function to minimize public tampering

15A1 15" All-in-one Touchcomputer Specifications

Case/Bezel Colour	Dark gray
Processor	Intel Celeron M 1GHz CPU with 400 MHz FSB
Chipset	Intel 915GME/ICH6
Video	Intel GMA 900 up to 128MB shared ⁱ
Memory (RAM)	512MB DDR2 standard on 1 of 2 slots; expandable to 1.5GB max ⁱⁱ
Supported Operating Systems	Microsoft Windows XP Professional Service Pack 2 Microsoft Windows Embedded for Point of Service (WEPOS)
Serial Ports	2 x RS232 serial (RJ45, 8 position); COM2 is RS232, RS422 and RS485 selectable
USB Ports	4 x 2.0 high-speed USB self powered: 1 (of 4) port is 12V USB (1.5A) for POS peripherals
VGA Port	1 x VGA D-SUB
Ethernet 100/10Base-T Port	1 x LAN RJ45
Cash Drawer Port	1 x cash drawer (RJ11, 6 position)
PS/2 Port	1 x PS/2 Universal (default to keyboard compatibility)
Audio Port	1 x 3.5 mm audio-out; 1 x 3.5 mm mic-in
Hard Disk Drive	1 x 2.5" 40 GB ⁱⁱⁱ SATA hard drive
Display	Size: 15.0 in. diagonal; Type: Active matrix TFT LCD; Aspect Ratio: 4 x 3
Optional Touchscreens	AccuTouch five-wire resistive, IntelliTouch surface wave, CarrollTouch infrared, or Acoustic Pulse Recognition (APR)
Optional Peripherals	Magnetic Stripe Reader (3 Track); Serial Customer Display (20x2 VFD)
Useful Screen Area	Horizontal: 304 mm (11.98 in.); Vertical: 228 mm (8.98 in.)
Maximum Touchcomputer Dimensions with Stand ^v	Width: 355 mm (13.97 in.) Height: 286 mm (11.27 in.) Depth: 278 mm (10.95 in.)
Optimal Resolution	1024 x 768 at 60Hz (native); scalar support for 800 x 600 at 60Hz
Colours	16.2 million
Brightness (typical)	No Touchscreen: 250 cd/m ² with AccuTouch: 200 cd/m ² with IntelliTouch: 230 cd/m ² with CarrollTouch: 230 cd/m ² with APR: 230 cd/m ²
Viewing Angle (typical, from center)	Horizontal (left/right): ±70° or 140° total Vertical (up/down): ±60°/55° or 115° total
Contrast Ratio	500:1 (typical)
Temperature	Operating: 0°C to 35°C; Storage: -20°C to 60°C
Humidity (non-condensing)	Operating: 20% to 80%; Storage: 5% to 95%
Weight With All Options	Actual: 7.8 kg (17.2 lbs); Shipping: 10.2 kg (22.5 lbs)
Agency approvals	UL/cUL (Recognized component), FCC, CE, VCCI, C-tick, EN60950
Warranty	2 years limited for touchcomputer and 1 year for hard disk drive and accessories (whether included in the touchcomputer or sold separately) ^v
Backlight Lamp Time to 1/2 Brightness	Minimum 30,000 hours
MTBF (mean time between failures)	50,000 hours demonstrated
Other Features	75mm VESA mounting; accessible HDD; removable base; threaded holes on bottom of base for secure mounting; 2 watt/channel speakers located in display head; touchscreen sealed to bezel; touchscreen sealed to LCD
Power Supply	External brick; Input (line) voltage: 100-240 VAC, 50-60 Hz; Output voltage/current: 12 V at 10.0 amps max.

ⁱ Memory supports both system and video. Accessible system memory may be up to 128 MB less than the amount stated, depending on the video mode.

ⁱⁱ Maximum memory

ⁱⁱⁱ GB equals one billion bytes when referring to storage capacity. Accessible capacity may be less.

^{iv} Dimensions vary with stand position and options selected.

^v Other restrictions and regional differences may apply. For a copy of the terms and conditions of the Elo TouchSystems Limited Warranty, please contact your Elo representative or reseller.

Find out more about the extensive range of Elo touch solutions. Go to www.elotouch.eu or simply call the office nearest you.

Corporate Headquarters

Tel +1 650 361 4800
Fax +1 650 361 4722
eloinfo@elotouch.com
www.elotouch.com

European Headquarters

Tel +32 16 35 21 00
Fax +32 16 35 21 01
elosales@elotouch.com
www.elotouch.eu

Asia-Pacific Headquarters

Tel +81 45 478 2161
Fax +81 45 478 2180
info@tps.co.jp
www.tps.co.jp

Latin America Headquarters

Tel +1 786 923 0251
Fax +1 305 931 0124
eloinfo@elotouch.com
www.elotouch.com.ar



Tyco Electronics Corporation reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

AccuTouch, Acoustic Pulse Recognition, CarrollTouch, IntelliTouch, Elo TouchSystems, TE logo and Tyco Electronics are trademarks. Windows is a registered trademark of Microsoft Corporation. Intel and Celeron are trademarks of Intel Corporation. All other trademarks are the property of their respective owners.
© 2008 Tyco Electronics Corporation 01/08.



Tyco Electronics

Our commitment. Your advantage.