



17A2 17" All-in-one Touchcomputer

Extended Versatility for POS Applications

Elo TouchSystems 17A2 17" all-in-one touchcomputer

provides an attractive ultra-compact 17" touch solution that can fit virtually anywhere in any point-of-service environment.

Expanded versatility, bigger screen, and improved serviceability all in a compact design

The 17A2 touchcomputer with dual video display support includes a choice of Elo TouchSystems newest breakthrough touch technology, Acoustic Pulse Recognition, AccuTouch five-wire resistive, IntelliTouch surface wave or CarrollTouch infrared. Its 1280 X 1024 SXGA resolution with a 5 x 4 aspect ratio displays clear, precise graphics for improved readability. A variety of optional field-replaceable peripherals can easily be integrated into the 17A2's compact design including: magnetic stripe reader, vacuum fluorescent, rear-facing LED customer display, biometric fingerprint recognition device, and speaker bar with/without a built-in single or omni-directional barcode scanner.

Designed for public access

The silent, fanless, spill and tamper resistant design of the 17A2 and its compact integrated peripherals, make this touchcomputer an ideal choice for point-of-sales, kiosks and point-of-interest applications.

Features

- Space saving, integrated, all-in-one touchcomputer with the footprint of a standard 17" LCD display
- Silent, fanless Intel® Celeron® M design, ideal for POS, kiosks and POI applications
- Industry standard VESA mounting options, configurable as a desktop or wall-mount
- Choice of Microsoft® Windows® Embedded for POS (WEPOS), XP Professional or Microsoft Windows XP Embedded operating systems
- Full range of "field" replaceable and serviceable POS options such as an integrated MSR, vacuum fluorescent, rear-facing LED customer display, biometric fingerprint recognition device, and speaker bar with/without a built-in single or omni-directional barcode scanner
- Available with AccuTouch five-wire resistive, CarrollTouch infrared, IntelliTouch surface-wave or Acoustic Pulse Recognition (APR) touch technology
- Integrated (optional) wireless LAN & DVD for expanded access and advanced media applications
- One Ethernet, two serial, and four high-speed USB 2.0 ports for maximum expansion
- Designed for public access with cables hidden from user's view; OSD and cable lockout function to minimize public tampering



Our commitment. Your advantage.

17A2 17" All-in-one Touchcomputer Specifications

Case/Bezel colour	Dark Gray
Processor	Intel Celeron M 1GHz CPU with 400 MHz FSB
Chipset	Intel 915GME/ICH6
Video	Up to 128MB shared ⁱ
Memory (RAM)	512MB DDR2 standard on 1 of 2 slots; Expandable to 1.5GB maximum ⁱⁱ
Supported Operating Systems	Microsoft Windows XP Professional Service Pack 2 Microsoft Windows Embedded for Point of Service (WEPOS) Microsoft Windows XP Embedded ⁱⁱⁱ
Serial Ports	2 x RS232 serial (RJ45, 8 position); COM2 is RS232, RS422 and RS485 selectable
USB Ports	4 x 2.0 high-speed USB self powered: 1 (of 4) port is 12V USB (1.5A) for POS peripherals
VGA Port	1 x VGA D-SUB
Ethernet 100/10Base-T Port	1 x LAN RJ45
Cash Drawer Port	1 x cash drawer (RJ11, 6 position)
PS/2 Port	1 x PS/2 Universal (default to keyboard compatibility)
Audio Port	1 x 3.5mm audio-out; 1 x 3.5mm mic-in
Hard Drive	1 x 2.5" 40 GB SATA hard drive ^v
Compact Flash Slot	1 x Compact Flash type I (internal)
Display Size	17.0 in. diagonal; Type: Active matrix TFT LCD; Aspect Ratio: 5 x 4
Optional Touchscreens	AccuTouch five-wire resistive; IntelliTouch surface wave; CarrollTouch infrared; Acoustic Pulse Recognition (APR)
Optional Peripherals	Magnetic Stripe Reader, Serial Customer Display; (20x2 VFD), Biometric Fingerprint Reader, Speaker Bar; Line or Omni Barcode Scanner, DVD Burner, drive (internal); Wireless Card
Useful screen area	337.92 mm (13.31 in.); 270.33 mm (10.65 in.)
Maximum Touchcomputer Dimensions with Stand ^v	Width: 391 mm (15.40 in.); Height: 380.6mm (15.00 in.); Depth: 239 mm (9.42 in.)
Tilt Adjust	From -5° to 75°
Optimal resolution	1280 x 1024 at 60Hz (native); scalar support for 1024 x 768 or 800 x 600 at 60Hz
Colours	16.7 million colours
Brightness (typical)	No Touchscreen: 300 cd/m ² with AccuTouch: 240 cd/m ² with IntelliTouch: 276 cd/m ² with CarrollTouch: 276 cd/m ² with APR: 276 cd/m ²
Viewing Angle (from center)	Horizontal (left/right): ±80° or 160° total; Vertical (up/down): ±80° or 160° total
Contrast Ratio	800:1 (typical)
Temperature	Operating: 0°C to 35°C; Storage: -20°C to 60°C
Humidity (non-condensing)	Operating: 20% to 80%; Storage: 5% to 95%
Weight With All Options (approx.)	Actual: +20 lb. (+9.09 kg); Shipping: +25 lb. (11.36 kg)
Agency Approvals	UL/cUL(Recognized component), FCC, CE, VCCI, C-tick, EN60950
Warranty	2 years limited for touchcomputer and 1 year for hard disk drive and accessories (whether included in the touchcomputer or sold separately) ^{vi}
Backlight Lamp Time to 1/2 Brightness	Minimum 50,000 hours
MTBF (mean time between failures)	50,000 hours demonstrated
Other Features	100mm VESA mounting; removable base; threaded holes on bottom of base for secure mounting; 2 watt/channel speakers located in display head; touchscreen sealed to bezel; touchscreen sealed to LCD
Power Supply	External brick; Input (line) voltage: 100-240 VAC, 50-60 Hz; Output voltage/current: 12 V at 10.0 amps max.

ⁱ Memory supports both system and video. Accessible system memory may be up to 128 MB less than the amount stated, depending on the video mode.

ⁱⁱ Maximum memory using 2 slots.

ⁱⁱⁱ Available for special orders only. Contact Elo Sales Representative or your Value-Added Reseller for details.

^{iv} GB equals one billion bytes when referring to storage capacity. Accessible capacity may be less. May not be applicable for XP Embedded Systems.

^v Dimensions vary with stand position and options selected.

^{vi} Other restrictions and regional differences may apply. For a copy of the terms and conditions of the Elo TouchSystems Limited Warranty, please contact your Elo representative or reseller.

Find out more about the extensive range of Elo touch solutions. Go to www.elotouch.eu or simply call the office nearest you.

Corporate Headquarters

Tel +1 650 361 4800
Fax +1 650 361 4722
eloinfo@elotouch.com
www.elotouch.com

European Headquarters

Tel +32 16 35 21 00
Fax +32 16 35 21 01
elosales@elotouch.com
www.elotouch.eu

Asia-Pacific Headquarters

Tel +81 45 478 2161
Fax +81 45 478 2180
info@tps.co.jp
www.tps.co.jp

Latin America Headquarters

Tel +1 786 923 0251
Fax +1 305 931 0124
eloinfo@elotouch.com
www.elotouch.com.ar



Tyco Electronics Corporation reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

AccuTouch, Acoustic Pulse Recognition, CarrollTouch, IntelliTouch, Elo TouchSystems, TE logo and Tyco Electronics are trademarks. Windows is a registered trademark of Microsoft Corporation. Intel and Celeron are trademarks of Intel Corporation. All other trademarks are the property of their respective owners.

© 2008 Tyco Electronics Corporation 01/08.



Tyco Electronics

Our commitment. Your advantage.