



## 42-inch Interactive Digital Signage Display Comparison

*Thinner, Lighter and Higher Performance with More Touch Points*

Model	4200L	4201L
		
<b>40% Thinner</b>	5.2" depth	IntelliTouch: 3.1" depth; Optical 3.2" depth
<b>30% Slimmer</b>	1.76" border thickness	1.26" border thickness
<b>60% Energy Savings (monitor only: ON)</b>	230W	85W
<b>30% Lighter (w/o computer module)</b>	74.7 lb. (33.9 kg)	IntelliTouch: 48.8 lb. (22.2kg); Optical: 52.4 lb. (23.8 kg)
<b>Latest Display Technology</b>	Active matrix TFT LCD Contrast Ratio: 3500:1 Brightness: 450 nits (LCD panel), 405 nits (w/ touchscreen)	Active matrix TFT LCD with LED backlight Contrast Ratio: 4000:1 Brightness: 700 nits (LCD panel), 630 nits (w/ touchscreen)
<b>Lower Overall Dimensions (W x D x H)</b>	40.2" x 5.2" x 24.1" 1020 mm x 132 mm x 613 mm	IntelliTouch: 39.2" x 3.1" x 23.1" 995 mm x 77.7 mm x 588 mm Optical: 39.2" x 3.2" x 23.1" 995 mm x 80.7 mm x 588 mm
<b>Touch Technologies</b>	IntelliTouch SAW P/N E841203 Optical multi-touch P/N E505459	IntelliTouch SAW P/N E561836 Optical multi-touch P/N E107085
<b>Touch Point</b>	IntelliTouch: 1 Optical: 4	IntelliTouch: 1 Optical: 6
<b>Video inputs</b>	Analog VGA, HDMI	Analog VGA, HDMI, Display Port
<b>Stereo Speakers (both orientations)</b>	10W x 2	5W x 4 for stereo sound in portrait and landscape mode
<b>Computer Modules (performance)</b>	ECM I: Celeron Dual-Core 2.2GHz ECM2: Core 2 Duo 3.0GHz ECM3: Intel Core i5 2.5GHz	ECMG2-i3: Core i3 3.3GHz ECMG2-i5: Core i5 3.6GHz
<b>Price</b>	MSRP starting at \$2,650 Including 3 year warranty	MSRP starting at \$2,650 Including 3 year warranty