



Computer Modules for Interactive Digital Signage Touch Displays

Two optional Computer Modules (ECM1 and ECM2), available for integrated use with Elo Interactive Digital Signage Touch Displays are well-suited for interactive media delivery. These high performance optional computer modules run either an Intel Dual-Core or Core 2 Duo processor, and slide into a dedicated bay behind the touch display. The system is interoperable with content management servers and web-based consoles for seamless connection with the internet and applications such as multimedia sharing and electronic point-of-sale. The computer modules can support optimal partitioning of locally cached and network stored content, allowing developers to monitor and deploy content via device-to-device or Web connections.

The new IDS family consists of three edge-to-edge glass (zero-bezel) display sizes measuring 32" (3200L), 42" (4200L) and 46" (4600L). All include Acoustic Pulse Recognition (APR) touch technology, which is housed in a highly durable, tempered glass and steel chassis for reliable interactivity and performance in almost any public-access location. Elo APR technology recognizes touch on virtually the entire screen surface, offering full-screen interface navigation regardless of how the screen is touched (finger, prosthetics, stylus or pen) and a highly efficient display canvas for almost any commercial application.

Benefits

- A fully self-contained end-point solution when coupled with IDS touch displays
- Professional-grade hardware provides improved durability
- Standard operating platform supports a variety of client interfaces
- Proprietary design enables field installation in the display without cables
- Dual core processor facilitates a highly responsive graphical interface

Computer Modules for Interactive Digital Signage Touch Displays

Model	ECM1	ECM2
Module dimensions	Width: 11.3" (287 mm); Depth: 9" (229 mm); Height: 2.3" (58 mm)	
Processor	Intel Celeron Dual-Core E1500 2.2 GHz 512 KB L2 Cache	Intel Core 2 Duo E8400 3.0 GHz 6 MB L2 Cache
Chipset	Intel G41 Express	
Video	Intel GMA X4500	
BIOS	AMI	
Memory (RAM) Standard/max./slots	1 GB DDR2 DIMM on 1 of 1 slot	2 GB DDR2 DIMM on 1 of 1 slot
Hard Disk Drive	160 GB 2.5" SATA	
Operating Systems Supported	Windows XP; No OS	
Languages	Win XP: 24 language groups: Arabic, Brazilian, Chinese (Simplified), Chinese (Traditional), Chinese (Hong Kong), Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish	
USB Port(s)	4 Type A ports	
Ethernet Port(s)	1 Gigabit LAN RJ45	
Audio Port(s)	3.5mm TRS jacks for Audio In, Audio Out, Microphone In	
Rear I/O (Summary of all above ports)	4 Type A USB ports 1 Gigabit Ethernet LAN RJ45 port 3 3.5 mm TRS jacks for Audio In, Audio Out, Microphone In	
Real Time Clock	Replaceable lithium-ion battery for clock	
Power supply	Power supplied by Digital Signage monitor	
Power consumption	150 W max	
Weight	Actual: 5.5 lb (2.6 kg) Shipping: 6.4 lb (2.9 kg)	
Shipping box dimensions	TBA	
Temperature	Operating: 0°C to 40°C (32°F to 104°F) Storage: -20°C to 50°C (-4°F to 122°F)	
Humidity (non-condensing)	Operating: 20-80%; Storage: 10-90%	
Agency approvals	US UL, FCC; Canada cUL, IC; Europe CE; Australia/New Zealand C-tick; China CCC; Japan VCCI; International CB	
Warranty	3 years	
MTBF	50,000 hours demonstrated	

To find out more about Elo's extensive range of touch solutions, go to www.elotouch.com, or call the office nearest you.

North America

Elo TouchSystems
301 Constitution Drive
Menlo Park, CA 94025-1110

800-ELO-TOUCH
Tel 1-650-361-4800
Fax 1-650-361-4722
customerservice@elotouch.com

Europe

Tel +32 (0)16 35 21 00
Fax +32 (0)16 35 21 01
elosales@elotouch.com

Asia-Pacific

Tel +81 (45) 478-2161
Fax +81 (45) 478-2180
www.tps.co.jp

Latin America

Tel 786-923-0251
Fax 305-931-0124
www.elotouch.com.ar



Tyco Electronics reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Elo (logo), Elo TouchSystems, TE (logo) and Tyco Electronics are trademarks of the Tyco Electronics group of companies and its licensors.

Copyright 2010 Tyco Electronics Corporation 05/10

