



iTouch Surface Wave

The Ultimate Touch Technology for CRTs

iTouch touchmonitors, utilizing patented touch-on-tube surface wave technology, are the ultimate, picture-perfect touch solution for applications that demand high image quality. Touches are sensed through surface waves on the CRT faceplate itself. By completely eliminating the touchscreen overlay, iTouch preserves 100% of the original picture quality, including clarity, colors, and brightness, and reflections are reduced by up to 80% compared with a traditional touchscreen overlay. With its super-sensitive, stable, drift-free operation and no parallax, our iTouch touchmonitors guarantee a touch response that is on target. Elo CRT touchmonitors with iTouch are available in desktop and open frame chassis configurations from 15" to 19".

Benefits

- No overlay - touch the tube directly!
- Preserves 100% of the original image quality
- Up to 20% brighter and 80% less reflection
- No overlay to break
- Continues to work even if scratched

Applications

- Kiosks
- Gaming and amusement
- Digital photo print stations
- Medical imaging
- Light industrial

iTouch Surface Wave Specifications

MECHANICAL

Input Method	Finger or gloved hand (cloth, leather, or rubber) activation
Available Sizes	15" to 19"; visit our Web site for full specifications and other offerings

ELECTRICAL

Positional Accuracy	Standard deviation of error is less than 0.080 in. (2 mm)
Resolution	Touchpoint density is based on controller resolution of 4096 x 4096, plus 255 levels corresponding to touch pressure
Touch Activation Force	Typically 2 to 3 ounces (55 to 85 grams)
Controller	Board: Serial (RS232) and USB

OPTICAL

Light Transmission	100%
--------------------	------

ENVIRONMENTAL

Temperature	Operating: 5°C to 55°C (rear-mount); 0°C to 40°C (desktop) Storage: -20°C to 65°C (rear-mount); -40°C to 60°C (desktop)
Relative Humidity	Operating: 40°C at 90% RH, noncondensing
Altitude	Operating: 10,000 ft (3,048 m) Storage/transport: 50,000 ft (15,240 m)
Chemical Resistance	The touch active area of the touchmonitor is resistant to chemicals that do not affect glass, such as: acetone, toluene, methyl ethyl ketone, isopropyl alcohol, methyl alcohol, ethyl acetate, ammonia- based glass cleaners, gasoline, kerosene, vinegar
Electrostatic Protection	Per EN 61000-4-2, 1995: Meets Level 4 (15 kV air/8 kV contact discharges)
Agency Approvals	UL, cUL, TÜV, CE, FCC Class A
Sealability	Can be sealed to meet NEMA 3/3R/5/12/12K/13, IP64 standards; Elo kiosk and gaming iTouch monitors include a watertight seal.

DURABILITY

Surface Durability	Surface durability is that of glass, Mohs' hardness rating of 7
Expected Life	No known wear-out mechanism, as there are no layers, coatings, or moving parts. iTouch technology has been operationally tested to more than 50 million touches in one location without failure, using a stylus similar to a finger.
Warranty	See monitor warranty



Touch the iTouch tube directly—no touchscreen overlay needed

Find out more about the extensive range of Elo touch solutions. Go to www.elotouch.eu or simply call the office nearest you.

Corporate Headquarters

Tel +1 650 361 4700
Fax +1 650 361 4747
eloinfo@elotouch.com
www.elotouch.com

European Headquarters

Tel +32 16 35 21 00
Fax +32 16 35 21 01
elosales@elotouch.com
www.elotouch.eu

Asia-Pacific Headquarters

Tel +81 45 478 2161
Fax +81 45 478 2180
info@tps.co.jp
www.tps.co.jp

Latin America Headquarters

Tel +1 305 428 5210
Fax +1 305 717 4909
eloinfo@elotouch.com
www.elotouch.com.ar



Tyco Electronics Corporation reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

AccuTouch, COACH, Elo TouchSystems, IntelliTouch, TE Logo, and Tyco Electronics are trademarks.
Copyright 2007 Tyco Electronics Corporation 8/07.



Our commitment. Your advantage.