




40 years ago we invented
the touchscreen.

Today we're reinventing how people use
them to pay, work and play.



elotouch.com

A high-angle, blurred photograph of a busy office atrium, overlaid with a semi-transparent green filter. The image shows a large, multi-level space with glass railings and a dense crowd of people moving through the area. The text "Why work with a leader?" is centered in white, sans-serif font.

Why work
with a
leader?

Elo, a pioneer in touchscreen technology, manufactures a complete line of touchscreen solutions that simplify the interface between people and computers. Our solutions are designed for the demanding requirements of diverse markets and applications across the globe.

Leader in innovation and quality

We invented the touchscreen more than 40 years ago and we have been a pioneer of touch technology ever since. Today, our products feature some of the latest touchscreen technology and come in a wide variety of configurations and forms. Elo touchscreen products are state-of-the-art, with high-quality displays, stable, drift-free operation, consistent reliability and durability. And we pay attention to the finest details, so our customers consistently receive the best in engineering too.

Leader in touchscreen technology

Elo is a leading global supplier of touch-enabled technology, products and industry solutions. The Elo portfolio encompasses the broadest selection of OEM touchscreen components as well as complete touchmonitors and all-in-one touchcomputers.

Our products are found in 80 countries across the globe in gaming machines, hospitality systems, industrial automation, interactive kiosks, healthcare, office equipment, point of sale terminals, retail displays and transportation applications.

Leader in service and support

We make doing business with us easy. Our sales team, service team and distribution partners are all organized to be fast, competent and close to you. Our teams and our partners' teams help ensure there is a technical support center or an office close to you with people who speak your language. And, our customization department is dedicated to developing bespoke solutions specific to your request.

- Over 40 years experience in the touchscreen industry
- Broad offering of touch technologies for virtually any application
- Consistently reliable, accurate, and durable products
- Stable, drift-free operation; scratch-resistant
- Recognized durability and performance
- Wide variety of configurations and form factors for design flexibility
- First-class service and support with worldwide sales people, sales partners, technical support and warehouses
- Custom solutions for special requirements
- Worldwide agency approvals

An overview of our touch solutions



PayPoint®

- Available with Windows, Android or for iPad
- Sleek, modern style built to last
- Peripherals are built in rather than bolted on – includes the register, cash drawer, MSR, barcode scanner, receipt printer and customer facing display
- Flip-for-signature touch screen and electronic receipt delivery



Tablet

- 10" Projected Capacitive (PCAP) touchscreen
- Rugged and connected
- Windows / Intel architecture
- Integrated MSR, barcode reader, smart card reader
- Docking station



Desktop Touch Displays

- Wide range of sizes from 7" to 24"
- Choice of touchscreen technologies, single touch & interactive touch
- Standard and wide-screen formats
- Models with seamless zero-bezel design (uninterrupted surface area)
- Base can be reversed or removed for wall-mount
- Retail, Hospitality and Healthcare models (certified globally)
- Integrated peripherals



Open-frame and Wall-Mount Touch Displays

- Wide range of sizes from 12" to 42"
- Multiple mounting options include rear-mount, VESA mount, panel-mount, front-mount and rack-mount
- Standard and wide-screen formats
- Integrated precision mini-bezel with watertight 0.5mm seal
- Compact and easy to integrate
- Choice of touchscreen technologies, single touch & interactive touch



All-in-One Touchcomputers

- 15", or 17", standard aspect ratio; 15", 19", 20", 22" wide-screen format
- Space-saving models with computing functionality integrated in the footprint of a standard LCD monitor and models designed for POS
- Models with seamless zero-bezel design (uninterrupted surface area)
- Field-installable peripherals such as magnetic stripe reader, customer display, inger print reader and barcode scanner
- Choice of touchscreen technologies, single touch & multi-touch



Interactive Digital Signage Displays

- 10", 15", 22", 32", 42", 55" and 70"
- Optional field-installable computer modules in various configurations
- Wall-mount, optional stand for desktop use
- Landscape or portrait orientation
- Pure-glass touchscreens for superior image quality
- Choice of touchscreen technologies, single touch & multi-touch



Components


- Touchscreens, touchscreen controllers and drivers
- Wide range of sizes from small to large
- Touchscreen technologies include:
5-Wire Resistive, Surface Acoustic Wave, Projected Capacitive (PCAP), Capacitive and Infrared



Turn opportunities into reality with our custom solutions

Standard touch solutions do not always address your specific needs. That's why Elo has the capability to develop specialized touch solutions specific to your environment.

With more than 40 years of experience and over 20 million touchscreen solutions installed across the globe we can develop exactly what you're looking for.



Some examples of our customization options:

- Different screen sizes and configurations
- Custom finishes and colors
- Private labeling
- Custom enclosures
- Sealing and shielding
- Special cabling
- Global agency certifications: UL, CSA, cUL, FCC, CE, CISPR, CTICK, VDE, and TÜV
- ... or any other customization you need

All it takes is talking to us!



Working from your specifications, we can quickly develop unique products that integrate seamlessly into your system and environment. Our staff oversees all the details from prototyping through production.

With an in-house mechanical design and prototyping staff we design and build “proof-of-concept” models and even short-run production parts. And our in-house compliance engineering staff is knowledgeable in all agency issues.

A touchscreen technology for every application

Technology	Benefits	Applications
Projected Capacitive (PCAP)	<ul style="list-style-type: none"> • Interactive multi-touch experience • Available in zero-bezel fully flat glass front surface • No known wear-out mechanism • Fast, accurate performance • Works with gloves • Easy care and cleaning, dust and liquid resistance 	<ul style="list-style-type: none"> • Retail & hospitality automation • Point-of-Information (POI) • Ticketing machines • Office automation • Point-of-Sale (POS) terminals • Kiosks
IntelliTouch® Surface Acoustic Wave (SAW)	<ul style="list-style-type: none"> • Pure glass construction delivers the ultimate in image quality • Stable, drift-free operation • Continues to work even if scratched • Sensitive touch response 	<ul style="list-style-type: none"> • Kiosks • Ticketing machines • Gaming machines • Light industrial • Office automation • Interactive digital signage • Point-of-Sale (POS) terminals
AccuTouch® Five-wire Resistive	<ul style="list-style-type: none"> • Stable, drift-free operation • Broad input flexibility • Contamination resistance • Accuracy in high-use applications • Long product life • Meets NEMA 4/4x/12 and IP 65 standards 	<ul style="list-style-type: none"> • Point-of-Sale (POS) terminals • Voting machines • Industrial automation • Medical equipment • Office automation • Retail automation • Pharmacy automation
SecureTouch® Anti-vandal Surface Acoustic Wave	<ul style="list-style-type: none"> • Tempered, heat or chemically strengthened glass • High impact resistance (about 2.5 times stronger than IntelliTouch) • Meets UL-60950 ball drop test • Privacy filter option 	<ul style="list-style-type: none"> • ATMs • Ticketing machines • Kiosks

Elo has one of the widest portfolio of touchscreen technologies, each optimized for different operating characteristics and environments to suit your application requirements.

Technology	Benefits	Applications
<p>Optical Touch</p> 	<ul style="list-style-type: none"> • Multi-touch response • Superb transparency and color fidelity • No wearing • Works with any input device • High resolution and accuracy 	<ul style="list-style-type: none"> • Interactive digital signage • Kiosks • Self-service • Education, museums • Gaming machines
<p>Surface Capacitive</p> 	<ul style="list-style-type: none"> • Elo proprietary narrow Z-border for enhanced linearity • Fast, sensitive touch response with excellent dragging performance • Compatible with industry standard protocols including Elo SmartSet protocol 	<ul style="list-style-type: none"> • Point-of-Sale (POS) terminals • Gaming/Amusement • Kiosk
<p>CarrollTouch Infrared</p> 	<ul style="list-style-type: none"> • Low profile, high resolution • No parallax • High durability, vandal resistance, and safety • Sealable from contaminants • Operates in extreme environments 	<ul style="list-style-type: none"> • Food processing • Industrial automation • Medical equipment • In-vehicle and transportation • Point-of-Sale (POS) terminals

Desktop Touchmonitor Product Portfolio



0700L – 7"



1002L



1215L – 12"

Color	Black	Black	Grey
Touch technology	AccuTouch, no touch	PCAP, no touch	AccuTouch, IntelliTouch
Contrast ratio	500:1	700:1	500:1
Panel brightness	200 nits	350 nits	200 nits
Viewing angle	140°/100°	170°/170°	140°/100°
Thickness	1.22 inches/31mm	1.14 inches/29 mm	2.08 inches/53mm
Comments	For use as second customer display or main display for small-screen applications	Optional MSR, NFC reader, barcode reader, multiple mounting options	



1502L



1509L - 15"



1515L – 15"

Color	Black	Black	Grey
Touch technology	PCAP	IntelliTouch	AccuTouch, IntelliTouch
Contrast ratio	700:1	300:1	700:1
Panel brightness	300 nits	220 nits	250 nits
Viewing angle	160°/160°	80°/40°	160°/140°
Thickness	1.29 inches/33 mm	2 inches/51mm	2.16 inches/55mm
Comments	Optional MSR, NFC reader, barcode reader. Full HD and HD versions		Optional MSR



1517L and 1523L – 15"



1715L – 17"



1717L and 1723 – 17"

Color	Black or white	Grey	Black or white
Touch technology	AccuTouch, AccuTouch Zero-Bezel, IntelliTouch, IntelliTouch Zero-Bezel, PCAP	AccuTouch, IntelliTouch	AccuTouch, AccuTouch Zero-Bezel, IntelliTouch, IntelliTouch Zero-Bezel, PCAP
Contrast ratio	700:1	800:1	1000:1
Panel brightness	250 nits	250 nits	250 nits
Viewing angle	160°/140°	160°/160°	170°/160°
Thickness	1.96 inches/50mm	2.24 inches/57mm	1.96 inches/50mm
Comments	Optional MSR, customer display 1523L: NRF/RFID; DVI; Speakers.	Optional MSR	Optional MSR, customer display 1723L: NRF/RFID; DVI; Speakers.



1915L - 19"



1919L - 19"



2201L - 22"

Color	Grey	Grey	Black
Touch technology	AccuTouch, IntelliTouch	AccuTouch, IntelliTouch, IntelliTouch Zero-Bezel, PCAP	IntelliTouch, IntelliTouch Zero-Bezel, PCAP
Contrast ratio	1000:1	1000:1	1000:1
Panel brightness	250 nits	250 nits	250 nits
Viewing angle	160°/160°	170°/160°	170°/160°
Thickness	2.40 inches/61mm	2.44 inches/62mm	2.08 inches/53mm
Comments		Wide-aspect (16:9); Speakers, field-installable MSR	Wide aspect (16:9); Optional MSR and webcam; Speakers



1929LM - 19"



2401LM - 24"

Color	White or black	White or grey
Touch technology	AccuTouch, IntelliTouch	IntelliTouch
Contrast ratio	2000:1	3000:1
Panel brightness	300 nits	300 nits
Viewing angle	178°/178°	178°/178°
Thickness	2.00 inches/51mm	2.44 inches/62mm
Comments	For medical applications.	For medical applications; Speakers

Open-frame Touchmonitor Product Portfolio



1247L – 12"



1537L – 15"



1739L – 17"

Aspect ratio	4:3	4:3	5:4
Contrast ratio	800:1	700:1	1000:1
Brightness (panel)	450 nits	250 nits	250 nits
Viewing angle	160°/140°	160°/140°	170°/160°
Native resolution	800 x 600 at 60 Hz	1024 x 768 at 60 Hz	1280 x 1024 at 60Hz
Touch technologies	IntelliTouch	AccuTouch, IntelliTouch, SecureTouch IntelliTouch Zero-Bezel, PCAP	AccuTouch, IntelliTouch, SecureTouch IntelliTouch Zero-Bezel, PCAP



1937L and 1930L – 19"



1939L and 1931L – 19"

Aspect ratio	5:4	5:4
Contrast ratio	1000:1	1000:1
Brightness (panel)	250 nits	250 nits
Viewing angle	170°/160°	178°/178°
Native resolution	1280 x 1024 at 60Hz	1280 x 1024 at 60Hz
Touch technologies	AccuTouch, IntelliTouch (1937L) IntelliTouch Zero-Bezel, PCAP (1930L)	AccuTouch, IntelliTouch, SecureTouch (1939L) IntelliTouch Zero-Bezel, PCAP (1931L)



1541L - 15"



1938L - 19"



1940L - 19"

Aspect ratio	16:9	16:10	16:9
Contrast ratio	500:1	1000:1	1000:1
Brightness (panel)	250 nits	250 nits	250 nits
Viewing angle	170°/130°	160°/160°	170°/160°
Native resolution	1366 x 768 at 60Hz	1440 x 900 at 60Hz	1366 x 768 at 60Hz
Touch technologies	AccuTouch, IntelliTouch	IntelliTouch	IntelliTouch, IntelliTouch Zero-Bezel, PCAP



2243L - 22"



2244L - 22"



2440L - 24"

Aspect ratio	16:9	16:9	16:9
Contrast ratio	1000:1	3000:1	3000:1
Brightness (panel)	250 nits	250 nits	250 nits
Viewing angle	170°/160°	178°/178°	178°/178°
Native resolution	1920 x 1080 at 60Hz	1920 x 1080 at 60Hz	1920 x 1080 at 60Hz
Touch technologies	IntelliTouch Zero-Bezel, PCAP	IntelliTouch Zero-Bezel, PCAP	IntelliTouch, IntelliTouch Zero-Bezel, PCAP



2740L - 27"



3243L - 32"



4243L - 42"

Aspect ratio	16:9	16:9	16:9
Contrast ratio	3000:1	3000:1	4000:1
Brightness (panel)	300 nits	350 nits	500 nits
Viewing angle	178°/178°	178°/178°	178°/178°
Native resolution	1920 x 1080 at 60Hz	1920 x 1080 at 60Hz	1920 x 1080 at 60Hz
Touch technologies	IntelliTouch, IntelliTouch Zero-Bezel	IntelliTouch, PCAP	IntelliTouch

Elo Tablet Product Portfolio



Elo Tablet 10.1"

Processor	Intel® Atom™ 1.6GHz Dual-Core N2600
Memory	2GB DDR3
Hard drive	32GB
Operating systems	No OS, Windows® 7
Touch technologies	PCAP
Comments	Optional Docking station with battery charging location. Integrated MSR, barcode reader (via rear facing auto focus camera), smart card reader, internal webcam, EMV ready.

Elo PayPoint® Portfolio



Elo PayPoint

Cash Drawer	5 bill trays, 6 coin compartments (configurable), mechanical locking key
Printer	Thermal 2 1/4" (58mm); accepts 2-inch (50mm) thermal paper roll
Bar Code Reader	1D Scanner
MSR	3-track encryptable set by software provider
Customer Facing Display	2 line, 16 character display
EMV	Communicates with a range of industry standard EMV devices
Software	Works with PayPoint certified software

All-in-One Touchcomputer Product Portfolio



X-15 - 15"



X-17 - 17"



X-20 - 20" Widescreen

Processor	Intel Celeron® 2.41 GHz Quad-Core J1900 / Intel Core i3 3.1 GHz 4350T; / Intel Core i5 2.0 GHz 4590T; / Intel Core i7 2.7 GHz 4790T
Memory	2GB-16GB depending on processor
Hard drive	320GB or 500GB HDD, 128GB or 256GB SSD"
Operating systems	No OS, Windows 7, POSReady 7, Windows 8.1, Windows 8.1 Retail, Win 10
Touch technologies	AccuTouch, IntelliTouch, IntelliTouch Zero-Bezel, PCAP (X20 available with PCAP only)
Comments	WiFi/Bluetooth standard, Optional MSR, 2x20 customer display, fingerprint reader, 1D bar code scanner, NFC reader, 2nd HDD (X3/5/7), rear facing display pole mount kit, I/O expansion module, wall mount kit



15B2 - 15" and 17B2 - 17"



15B3 - 15" and 17B3 - 17"



15E2 - 15"

Processor	Intel 1.86GHz Atom Dual-Core N2800	Intel 3.3GHz i3-3220 (Ivy Bridge)	Intel 2.41GHz J1800
Memory	2GB DDR3 (upgradeable to 4GB) SO-DIMM	2GB DDR3 (upgradeable to 8GB) SO-DIMM	2GB DDR3 (upgradeable to 4GB)
Hard drive	320GB	320GB	320GB HDD or 128GB SSD
Operating systems	No OS, Windows 7	No OS, Windows 7	No OS, Windows 7, POSReady 7, Windows 8.1, Windows 8.1 Retail
Touch technologies	AccuTouch, IntelliTouch Zero-Bezel	AccuTouch, IntelliTouch Zero-Bezel	AccuTouch, IntelliTouch Zero-Bezel
Comments	Fanless, optional MSR, customer display, fingerprint reader, wireless, 2nd HDD, 7-inch rear-facing touch LCD	Optional MSR, customer display, fingerprint reader, wireless, 2nd HDD, 7-inch rear-facing touch LCD	Optional MSR, customer display, 2x20 customer display, 7-inch rear-facing touch LCD



19C5 - 19" and 22C5 - 22"



19C2 - 19" and 22C2 - 22"



19C3 - 19" and 22C3 - 22"

Processor	Intel Core™ 3.0GHz i5-3550S	Intel Atom 1.86GHz Dual-Core N2800	Intel 3.3GHz i3-3220 (Ivy Bridge)
Memory	4GB DDR3 (expandable to 8GB)	2GB DDR3 (upgradeable to 4GB)	2GB DDR3 (upgradeable to 8GB)
Hard drive	320GB	320GB	320GB
Operating systems	Windows 7, Windows 8.1	Windows 7	Windows 7
Touch technologies	IntelliTouch Zero-Bezel	AccuTouch, IntelliTouch Zero-Bezel	AccuTouch, IntelliTouch Zero-Bezel, PCAP
Comments	Optional MSR, customer display, fingerprint reader, wireless, 2nd HDD, 7-inch rear-facing touch LCD	Fanless, optional MSR, customer display, fingerprint reader, wireless, 2nd HDD, 7-inch rear-facing touch LCD	Fanless, optional MSR, customer display, fingerprint reader, wireless, SSD, 2nd HDD, 7-inch touch LCD

Interactive Digital Signage (IDS) Product Portfolio



1001L – 10"



1501L – 15"



2201L – 22"



Enclosure	Black; portrait, landscape and tabletop	Black; portrait, landscape and tabletop	Black; portrait, landscape and tabletop
Display ratio	16:10; 1280 x 800	16:9; 1920 x 1080 (Full HD)	16:9; 1920 x 1080 (Full HD)
Form factor	Wall mount; floor-, pole- and desktop stands	Wall mount; floor-, pole- and desktop stands	Wall mount; floor-, pole- and desktop stands
Thickness	0.9" (25mm)	1.1" (30mm)	1.4" (38mm)
Contrast ratio	800:1	700:1	1000:1
Brightness (typical)	350 nits panel	300 nits panel	250 nits panel
Viewing angle	170°/170°	160°/160°	178°/178°
Touch technologies	PCAP	PCAP	PCAP
Comments	WiFi, Bluetooth, 3G/4G; multiple accessories and mounting options available. EloView Remote Management compatible	WiFi, Bluetooth, 3G/4G; multiple accessories and mounting options available. EloView Remote Management compatible	WiFi, Bluetooth, 3G/4G; multiple accessories and mounting options available. EloView Remote Management compatible



3201L – 32"



4201L – 42"



5501LT – 55"



Enclosure	Black; portrait, landscape and tabletop	Black or white; portrait, landscape and tabletop	Black; portrait or landscape capable
Display ratio	16:9; 1920 x 1080 (Full HD)	16:9; 1920 x 1080 (Full HD)	16:9; 1920 x 1080 (Full HD)
Form factor	Wall mount with optional desktop stand	Wall mount with optional desktop stand	Wall mount
Thickness	2.8" (72mm)	3.1" (78mm)	3.4" (87mm)
Contrast ratio	3000:1	4000:1	4000:1
Brightness (typical)	350 nits panel	700 nits panel	500 nits
Viewing angle	178°/178°	178°/178°	178°/178°
Touch technologies	IntelliTouch, PCAP	IntelliTouch, Optical	Infrared
Comments	Optional webcam; VGA, HDMI display port video; four 5W speakers; NFC adapter, OPS kit, EloView Remote Management compatible	Optional webcam; VGA, HDMI display port video; four 5W speakers; NFC adapter, OPS kit, EloView Remote Management compatible	Optional webcam; VGA, HDMI display port video; four 5W speakers; NFC adapter, OPS kit, EloView Remote Management compatible



7001LT - 70"



Enclosure	Black; portrait or landscape capable
Display ratio	16:9; 1920 x 1080 (Full HD)
Form factor	Wall mount
Thickness	3.7" (94mm)
Contrast ratio	5000:1
Brightness (typical)	500 nits panel
Viewing angle	176°/176°
Touch technologies	Infrared
Comments	Optional webcam; VGA, HDMI display port video; four 5W speakers; NFC adapter, OPS kit, EloView Remote Management compatible



Android IDS Computer Module

Designed specifically for Elo's 3201L, 4201L, 5501LT, and 7001LT models. No cables required; seamless docking integration.

AECM: Qualcomm® Snapdragon™ APQ8064 CPU, 2 GB RAM, 16 GB flash 4x USB 2.0 ports, 1 GB LAN, Wi-Fi 802.11 b/g/n, Bluetooth 4.0, Antenna Included



ECMG2B IDS Computer Modules

Designed specifically for Elo's 3201L, 4201L, 5501LT, and 7001LT models. No cables required; seamless docking integration.

ECMG2B i3 Module. Intel® Core™ 4th Gen i3 3.4 GHz, HD4400 graphics, 2 GB RAM, 320 GB Hard Drive, Window 8.1, Windows 7, No O/S

ECMG2B i5 Module: Intel® Core™ 4th Gen i5 3.7 GHz, HD4600 graphics, 4 GB RAM, 320 GB Hard Drive, Window 8.1, Windows 7, No O/S

ECMG2B i7 Module Intel® Core™ 4th Gen i7 4.0 GHz, HD4600 graphics, 8 GB RAM, 320 GB Hard Drive Window 8.1, Windows 7, No O/S

Deploy your responsive websites and apps to stores across the country or globe.

Now, you can do it easily and securely with EloView. EloView software provides device setup, remote management, content scheduling, and the ability to securely upgrade the operating system, applications, and content.



Your Size, Your Style

Elo's large format products come with a variety of options. They can be a touch display, a computer, a wall-mounted unit or a bare-bones "kiosk-mounted" unit (32 or 42). They can be rugged single-touch or multi-touch.

IT-Friendly

Elo products come standard with a variety of peripherals, mounting and physical lockdown options that will delight your IT team. Additionally, we partner with a number of mobile device management ("MDM") and Content Management (CMS) partners.

Operate Your Way

Most products are available with Windows and Android computer options – with support for many other operating systems such as Linux, Chrome OS and Mac OS.



Elo is Everywhere.

With 20+ million installations in 80+ countries, we deliver professional touch, built to last.





To find out more about our extensive range of Elo touch solutions, go to elotouch.com, or call the office nearest you.

North America

Elo Touch Solutions
1033 McCarthy Boulevard
Milpitas, CA 95035

800-ELO-TOUCH

Tel +1 408 597 8000
Fax +1 408 597 8001
customerservice@elotouch.com

Europe

Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America

Tel 786-923-0251
Fax 305-931-0124
www.elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, EloView, AccuTouch, CarrollTouch, IntelliTouch, PayPoint and SecureTouch are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2016 Elo Touch Solutions, Inc. All rights reserved. 16011BEB00001

Medical and Healthcare Application Disclaimer: It is the sole responsibility of any person intending to commercialize, market or use any of Elo Touch Solutions, Inc. or its family of companies ("Elo") products for medical or healthcare applications to ensure that such product is adequate and appropriate for the person's intended use and complies with all applicable laws, regulations, codes and standards including but not limited to the European Union Medical Device Directive, United States Federal Food, Drug, and Cosmetic Act, regulations of the United States Food and Drug Administration (FDA), and other similar legislation in jurisdictions around the world, and for obtaining and maintaining any required regulatory approvals including but not limited to any required market clearances. Elo has not sought nor received any rulings from the FDA or any other federal, state, or local government agency or notified body as to the safety, effectiveness or appropriateness of its product for such applications. Persons intending to evaluate or use Elo's product for medical or healthcare purposes must rely on their own medical and legal judgment without any representation on the part of Elo. © 2016 Elo Touch Solutions, Inc. All rights reserved.

