


INTELLITOUCH® TOUCHSCREEN
SCN-IT-FLT24.0-002-007-R



NOTES:

1. ALL DIMENSIONS ARE IN INCHES AND MILLIMETERS.
2. GLASS THICKNESS: 0.12±0.012" [3.0±0.3mm].
3. TRANSDUCERS ARE LOCATED AT THE POSITIONS SHOWN. HEIGHT OF TRANSDUCER ABOVE GLASS: 3.0mm[0.120"] MAX.
4. NO MATERIAL EXTENDS MORE THAN 0.03"/0.8mm BEYOND THE BACK SURFACE OF THE GLASS.
5. CABLE ROUTING (ALONG THE TOP EDGE) ADDS 0.10"/2.5mm MAX. AS INDICATED ON THE SCREEN.
6. BERG 65043-031, 2x6 HOUSING WITH BERG 48239-000 RECEPTACLES, DIRECTLY MATES WITH ANY OF THE FOLLOWING:
-INTELLITOUCH SERIAL CONTROL BOARD
-012226 CABLE (2x6 TO 8" DB9 BULKHEAD)
7. THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.
8. CABLE JACKET STRIPPED 6.0" [152mm] FOR EASE DURING THE INTEGRATION PROCESS.
9. SURFACE QUALITY SPECIFICATION: ES500051 (LEVEL 2). ELLIPTICAL BUBBLES TO BE CLASSIFIED AS LINEAR DEFECTS. MAXIMUM LENGTH=12.5mm[0.5"] AND MAXIMUM WIDTH=0.25mm[0.01"].

CONNECTION CHART

PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE (+)	BLU	BLK
4	Y TRANSMIT (+)	BLU	GRY
5	Y RECEIVE (-)	BLK	BLK
6	Y TRANSMIT (-)	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT (-)	RED	RED
9	X RECEIVE (-)	RED	BLK
10	X TRANSMIT (+)	GRN	RED
11	X RECEIVE (+)	WHT	BLK
12	KEY		

TOUCHSCREEN TABULATION

PART NO	SURFACE FINISH
E201107	HIGH RESOLUTION ANTI-GLARE

T/D HEIGHT
0.12"[3.0mm]
MAXIMUM



MS600207
DATE:01/31/07
REV. B