
INTELLITOUCH® TOUCHSCREEN SCN-ST-FLT19.0-001-009-R



NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS AND INCHES.
- 2. CHEMICALLY STRENGTHENED GLASS THICKNESS: 5.6mm [0.22"] NOMINAL.
- TRANSDUCERS ARE LOCATED AT THE POSITIONS SHOWN. HEIGHT OF TRANSDUCERS ABOVE GLASS: 3.8mm/0.15" MAX.
- 4. NO MATERIAL EXTENDS MORE THAN 0.8mm/0.03" BEYOND THE BACK SURFACE OF THE GLASS.
- 5 CABLE IS ROUTED ON TOP SURFACE (ALONG THE EDGE) OF THE GLASS.
- 6 BERG 65043-031, 2x6 HOUSING WITH BERG 48239-000 RECEPTACLES, DIRECTLY MATES WITH ANY OF THE FOLLOWING:
 - -INTELLITOUCH SERIAL CONTROL BOARD -012226 CABLE (2x6 TO 8" DB9 BULKHEAD)
- 7. THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.

CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE (+)	BLU	BLK
4	Y TRANSMIT (+)	BLU	GRY
5	Y RECEIVE (-)	BLK	BLK
6	Y TRANSMIT (-)	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT (-)	RED	RED
9	X RECEIVE (-)	RED	BLK
10	X TRANSMIT (+)	GRN	RED
- 11	X RECEIVE (+)	WHT	BLK
12	KEY		

