

## NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS AND INCHES.
- 2. CHEMICALLY STRENGTHENED GLASS THICKNESS: 5.6±0.3mm [0.22±.012"].
- TRANSDUCERS ARE LOCATED AT THE POSITIONS SHOWN. HEIGHT OF TRANSDUCERS ABOVE GLASS SURFACE=3.2mm [.13"] MAX.
- 4. WIRES ARE ROUTED ON THE TOP SURFACE (ALONG THE EDGE) OF THE SCREEN.
- 6 BERG 65043-031, 2x6 HOUSING WITH BERG 48239-000 RECEPTACLES, DIRECTLY MATES WITH ANY OF THE FOLLOWING:
  -INTELLITOUCH SERIAL CONTROL BOARD
  -012226 CABLE (2x6 TO 8" DB9 BULKHEAD)

REFER TO  $\underline{\text{WWW.ELOTOUCH.COM}}$  FOR CONTROLLERS AND ACCESSORIES PART NUMBERS.

 THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.

CONNECTION CHART				
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR	
1	GROUND	OVERALL SHIELD		
2	KEY			
3	Y RECEIVE (+)	BLU	BLK	
4	Y TRANSMIT (+)	) BL	GRY	
5	Y RECEIVE (-)	BLK	BLK	
6	Y TRANSMIT (-)	YEL	GRY	
7	GROUND	INNER SHIELD		
8	X TRANSMIT (-)	RED	RED	
9	X RECEIVE (-)	RED	BLK	
10	X TRANSMIT (+)	GRN	RED	
11	X RECEIVE (+)	WHT	BLK	
12	KEY	·		

TOUCHSCREEN TABULATION		
PART NO	SURFACE FINISH	
E805321	ANTIGLARE	

