

8



▶▶▶ Replace the side door.

9



▶▶▶ Turn on the touchcomputer.

**Included Items:**

- 80GB SATA hard drive
- Four screws to mount hard drive
- Four grommets



# Quick Installation Guide

## Installing a Secondary Hard Drive for the D-Series Touchcomputer

**Caution:**  
Before installing the hard drive, make sure that the touchcomputer is powered off.



[www.elotouch.com](http://www.elotouch.com)



Revision A  
P/N E199284

**North America**  
Elo TouchSystem  
301 Constitution Drive,  
Menlo Park, CA 94025  
[www.elotouch.com](http://www.elotouch.com)

**Elo Technical Support**  
**Online self-help:**  
[www.elotouch.com/go/websupport](http://www.elotouch.com/go/websupport)  
**Technical Support contacts in your region:**  
[www.elotouch.com/go/contactsupport](http://www.elotouch.com/go/contactsupport)

**Europe**  
Tel +32 (0)16 35 21 00  
Fax +32 (0)16 35 21 01  
[elosales@elotouch.com](mailto:elosales@elotouch.com)

**Asia-Pacific**  
Tel +81 (45) 478-2161  
Fax +81 (45) 478-2180  
[www.tps.co.jp](http://www.tps.co.jp)

**Latin America**  
Tel 1-305-428-5210  
Fax 1-305-717-4909  
[www.elotouch.com.ar](http://www.elotouch.com.ar)



1



▶▶▶ Turn off the power to the touchcomputer.

2



▶▶▶ Remove the side door, as shown.

3




▶▶▶ Remove the front door.

4




▶▶▶ Remove the 2 screws and pull out the hard drive door.

5



▶▶▶ Push in the 4 grommets. Secure the drive with 4 screws.

6



▶▶▶ Add the power and data cable.

7



▶▶▶ Replace the hard drive door and the 2 screws.

8



▶▶▶ Replace the front door.