

LCD Open-Frame Touchmonitors

SPECIFICATIONS <i>Model</i>	1247L 12" LCD	1537L 15" LCD	1739 17" LCD	1939L 19" LCD	2039 20" LCD	2239 22" LCD	2639 26" LCD	3239 32" LCD
Case/bezel color	Galvanized sheet metal; black	Black minibezel	Steel/black	Steel/black	Black	Black	Black	Black
Display size	12.1" diagonal	15" diagonal	17" diagonal	19" diagonal	20" diagonal	22" diagonal	26" diagonal	32" diagonal
Brightness, LCD panel*	350 cd/m ²	250 cd/m ²	300 cd/m ²	250 cd/m ²	410 cd/m ²	300 cd/m ²	500 cd/m ²	500 cd/m ²
Viewing angle (H/V)	130°/105°	140°/115°	160°/160°	178°/178°	178°/178°	170°/160°	176°/176°	178°/178°
Contrast ratio	500:1	500:1	800:1	1000:1	600:1	1000:1	1500:1	1500:1
Power supply	External	External	External	External	Internal	Internal	Internal	Internal
<i>*Without touch</i>								

Touch Technologies

Applications


Elo TouchSystems Contacts



Acoustic Pulse Recognition (APR)

- Optics and durability of pure glass
- Unaffected by water, dust, grease
- Works even when scratched
- Works with a finger and hard stylus
- No wear-out mechanism

- Retail point of sale (POS) terminals
- Restaurant and hospitality
- Automation
- Industrial automation
- Office automation



AccuTouch Five-Wire Resistive

- Stable, drift-free operation
- Broad input flexibility
- Resistance to contamination
- Accuracy in high-use applications


- Retail Point-of-sale (POS) terminals
- Pharmacy automation
- Medical equipment
- Voting machines



Surface Capacitive

- Fast, sensitive touch response
- Excellent drag performance
- Transparent protective coating


- Kiosks
- Retail Point-of-sale (POS) terminals
- Gaming/amusement



CarrollTouch Infrared

- Low profile, high resolution
- High durability
- Sealable from contaminants
- Operates in extreme environments

- Retail Point-of-sale (POS) terminals
- Food processing
- Industrial automation
- Medical equipment



IntelliTouch Surface Wave

- Stable, drift-free operation
- Pure glass construction delivers the ultimate in image quality
- Continues to work even if scratched

- Kiosks
- Retail Point-of-sale (POS) terminals
- Pharmacy automation
- Digital photo print stations

North America

Elo TouchSystems
301 Constitution Drive
Menlo Park, CA 94025
Tel 1-800-ELO-TOUCH
(1-800-356-8682)
Fax 650-361-4722

Asia-Pacific

Touch Panel Systems K.K.
Sun Hamada Bldg. 2F
1-19-20 Shin-Yokohama
Kohoku-ku, Yokohama
Kanagawa 222-0033
Tel 81 (45) 478-2161
Fax 81 (45) 478-2180
www.tps.co.jp

Europe

Tyco Electronics Raychem NV
Diestsesteenweg 692
B-3010 Kessel-Lo
Tel 32 (0) 16 35 21 00
Fax 32 (0) 16 35 21 01
elosales@elotouch.com

Latin America

Elo TouchSystems
7300 N.W. 19th Street
Suite 313
Miami, FL 33126
Tel 1-305-428-5210
Fax 1-305-717-4909
www.elotouch.com.ar



Tyco Electronics

Users should independently evaluate the suitability of the products for their application. Accutouch, CarrollTouch, IntelliTouch, iTouch and APR are trademarks of Tyco Electronics Corporation.

©2008 Tyco Electronics Corporation 10/08

www.elotouch.com



LCD Desktop Touchmonitors

SPECIFICATIONS <i>Model</i>	1215L 12" LCD	1229L 12" LCD	1515L 15" LCD	1522L 15" LCD	1529L 15" LCD	1715L 17" LCD	1729L 17" LCD	1915L 19" LCD	1928L 19" LCD
Case/bezel color	Dark gray	Dark gray	Dark gray and beige	Dark gray and beige	Dark gray and beige	Dark gray	Dark gray and beige	Dark gray	Dark gray and beige
Display size	12.1" diagonal	12.1" diagonal	15" diagonal	15" diagonal	15" diagonal	17" diagonal	17" diagonal	19" diagonal	19" diagonal
Brightness, LCD panel*	200 cd/m ²	350 cd/m ²	250 cd/m ²	250 cd/m ²	350 cd/m ²	280 cd/m ²	300 cd/m ²	300 cd/m ²	300 cd/m ²
Viewing angle (H/V)	140°/110°	130°/95°	140°/115°	140°/120°	120°/100°	140°/123°	160°/160°	160°/160°	178°/178°
Contrast ratio	500:1	450:1	500:1	500:1	400:1	450:1	800:1	800:1	1300:1
Power supply	Internal	External	Internal	Internal	Internal	Internal	Internal	Internal	External
<i>*Without touch</i>		<i>*Optional MSR, biometric fingerprint reader, rear-facing customer display</i>	<i>*Optional Field Installable MSR</i>	<i>*Optional Field Installable MSR</i>	<i>*Optional MSR, biometric fingerprint reader, rear-facing customer display</i>		<i>*Optional MSR, biometric fingerprint reader, rear-facing customer display</i>		

LCD Desktop Touchmonitors

SPECIFICATIONS <i>Model</i>	1900L 19" LCD Zero-Bezel*	2420L 24" LCD	2620L 26" LCD	3220L 32" LCD	4220L 42" LCD
Case/bezel color	Beige or black	Black	Black	Black	Black
Display size	19" diagonal	24" diagonal	26" diagonal	32" diagonal	42" diagonal
Brightness, LCD panel*	300 cd/m ²	300 cd/m ²	500 cd/m ²	500 cd/m ²	500 cd/m ²
Viewing angle (H/V)	160°/160°	178°/178°	170°/170°	178°/178°	178°/178°
Contrast ratio	1000:1	1000:1	800:1	3000:1	3000:1
Power supply	Internal/External	Internal	Internal	Internal	Internal
<i>*Without touch</i>					
<i>*Zero-Bezel also available in a 22" model</i>					

LCD All-in-One Touchcomputers

SPECIFICATIONS <i>Model</i>	15A1 15" LCD Touchcomputer	15A2 15" LCD Touchcomputer	17A2 17" LCD Touchcomputer
Case/bezel color	Dark gray	Dark gray	Dark gray and beige
Display size	15" diagonal	15" diagonal	17" diagonal
Brightness, LCD panel*	250 cd/m ²	250 cd/m ²	300 cd/m ²
Viewing angle (H/V)	140°/115°	125°/140°	160°/160°
Contrast ratio	500:1	500:1	800:1
Power supply	External	External	External
Processor	Intel Celeron M 1GHz CPU	Intel Celeron M 1GHz CPU	Intel Celeron M 1GHz CPU
Memory (RAM)	512 MB DDR2 standard	1 GB DDR2 standard on 1 of 2 slots. Expandable to 2 GB max	512 MB DDR2 standard on 1 of 2 slots. Expandable to 1.5 GB max
<i>*Without touch</i>			
<i>*Optional MSR, rear-facing customer display</i>		<i>*Optional Field Installable MSR, rear-facing customer display, biometric fingerprint reader, omni or single line barcode scanner</i>	<i>*Optional Field Installable MSR, rear-facing customer display, biometric fingerprint reader, omni or single line barcode scanner</i>



1229L



1515L



1900L



2039L



17A2



1939L



15A1



1739L



1915L